

Eastside Sign Specifications

- Full ASCII character set (upper and lowercase letters, numbers and symbols)
- 5x7 pixel matrix for each character, fixed width font
- Displays one message at a time on the board with a maximum of 10 pages per message
- 14 messages stored in keyboard
- Hold and blink motion types with adjustable message duration and blink rates
- Displays the date and the time of day in 12 or 24 hour format
- 3 lines of 8" tall fixed width LED letter panels
- Each digital panel will be 80.5 inches long and have 15 character spaces
- Wireless programming from keyboard controller
- Name panel and logo illuminated with long lasting, low energy consumption white LED's, not fluorescent bulbs
- Optional temperature probe displays degrees in Fahrenheit or Celsius
- 66 key 900 MHz wireless keyboard controller
- Non-Volatile Memory (stores last message displayed)
- LED viewing angle: 140 degrees
- LED rating: 100,000 + hours
- LED colors available: red-630nm, or amber-592nm
- LED intensity adjustment: automatic or 8 levels controlled via keyboard
- Communications: 1000 ft
- Operating voltage: 120 or 240 VAC
- Power rating: 10 amps max (all LED's on)
- Operating temperature: -40 degrees to 122 degrees F/ -40 degrees to 50 degrees C
- Product Approval/Safety Listings: FCC approval/ETL, CSA Safety listing
- Case materials: UV resistant PVC and ABS plastic; UV resistant protective polycarbonate face
- 3 year factory warranty on electronics, 10 year warranty on other sign components
- Include delivery and installation
- The existing sign will be converted to a digital message center. The plastic faces of the existing sign will be removed, the fluorescent bulbs will be replaced with LED lights, and fixed width LED letter message panels will be installed.

**Warren County Board of Education
Bid Tab
Eastside Sign**

Firm Name: _____

Address: _____

City/State: _____

Telephone: _____

Authorized Signature: _____

E-mail address _____

ENCLOSE A COPY OF SPECIFICATIONS

Rebates _____

Comments: